

LUVOCOM 3F

Materials for Fused Filament Fabrication - Designed for Highest Performance

Reduced anisotropy

• Print in unheated chambers

• Made to match injection molded part performance



Product Overview LUVOCOM 3F

Material	Dalyman	Modification	Color	Further information
LUVOCOM® 3F PEEK 9581 NT LUVOCOM® 3F PEEK CF 9676 BK	PEEK PEEK	Modified neat 15% CF	Natural beige Black	rui tilei illioitilatioli
LUVOCOM® 3F PEEK GF 9761 BK	PEEK	15% GF	Black	
LUVOCOM® 3F PEKK 50082 NT	PEKK	Modified neat	Natural beige	
LUVOCOM® 3F PEI 50236 GY	PEI	Modified neat	Grey similar to RAL 7012	Meets UL94 V0 from 0.4mm* Meets EN 45545-2 R1 HL3 from 2mm**
LUVOCOM® 3F PPS CF 9938 BK	PPS	15% CF	Black	Meets UL94 V0 from 0.4mm* Meets EN 45545 R22, R23 HL3**
LUVOCOM® 3F PPS GF 50300 BK	PPS	25% GF	Black	
LUVOCOM 3F PA ^{HT®} 9825 NT	РДНТ	Modified neat	Natural white	
LUVOCOM 3F PAHT® 9875 NT LUVOCOM 3F PAHT® 9936 BK	PA ^{HT}	Modified neat Modified neat	Natural white Black	Minimized water uptake Optimized surface appearance
LUVOCOM 3F PAHT® KK 50056 BK FR	РАНТ	Ceramic spheres	Black	Meets UL94 V0 from 0.4mm* Meets EN 45545 R22, R23 HL3**
LUVOCOM 3F PA ^{HT®} CF 9742 BK	PAHT	15% CF	Black	
LUVOCOM 3F PA ^{HT®} CF 9891 BK	PAHT	15% CF	Black	Minimized water uptake
LUVOCOM 3F PAHT® CF 9743 BK	PAHT	25% CF	Black	
LUVOCOM 3F PAHT® GK 9874 NT	PAHT	10 % hollow glass spheres	Natural white	
LUVOCOM 3F PAHT® 9826 BK	PAHT	Tribological	Black	
LUVOCOM® 3F PET CF 9780 BK	PET	15% CF	Black	
LUVOCOM® 3F eco PET 50291 BK	PET	Modified neat	Black	Based on 90% recycled PET
LUVOCOM® 3F TPU CNT 9902 BK	TPU	CNT	Black	Electrically Conductive (ESD)
LUVOCOM® 3F PP CF 9928 BK LUVOCOM® 3F PP 9929 NT	PP PP	20% CF Modified neat	Black Natural white	

^{* 3}D printed specimen **Contact us for details



Product Overview LUVOCOM 3F Filament

LUVOCOM 3F Filament available in 1.75 and 2.85mm, 750g spools	Polymer	Modification	Color	Further information
LUVOCOM 3F Filament PA ^{HT®} 9825 NT	PAHT	Modified neat	Natural white	
LUVOCOM 3F Filament PA ^{HT®} 9936 BK	PAHT	Modified neat	Black	Optimized surface appearance
LUVOCOM 3F Filament PAHT® CF 9891 BK	PAHT	15% CF	Black	Minimized water uptake
LUVOCOM® 3F Filament PET CF 9780 BK	PET	15% CF	Black	

Where to buy:

Nexeo www.nexeo3d.com IGO3D www.igo3d.com



Further products are available on request or under development. What are your needs? We customize your 3D printing material.

3D PRINTING **MATERIA** Experience the 3Difference

LUVOCOM° 3F **FILAMENT**

Additive manufacturing solutions

- Extrusion based processes
- Product: filaments
- Carbon fiber reinforced and unreinforced materials

LUVOCOM® 3F

- Extrusion based processes
- Product: pellets
- Composite materials (CF, GF). tribological, electrically and thermally conductive

- Powder fusion processes
- Product: powder
- Nano-filled materials

Our Material Competences



STRUCTURAL









WEIGHT







RESISTANT TRIBOLOGICAL CONDUCTIVE

PROTECTION

SURFACE

CUSTOMIZED POLYMER MATERIALS

Europe & Head Office Lehmann&Voss&Co. KG

Alsterufer 19 20354 Hamburg Germany Tel +49 40 44 197 250 E-mail luvocom@lehvoss.de

North America

LEHVOSS North America, LLC 185 South Broad Street Pawcatuck, CT 06379 USA Tel +1 855 681 3226 E-mail info@lehvoss.us

LEHVOSS (Shanghai) Chemical Trading Co., Ltd Unit 4805 Maxdo Centre 8 Xingyi Road Changning District Shanghai 200336 China Tel +86 21 6278 5181



www.luvocom3F.com

E-mail info@lehvoss.cn